

HIGH PERFORMANCE

UNIVERSAL USAGE

EFFICIENCY

EASE OF USE

FEATURES & BENEFITS:



Substrate versatility

Broad range of core/foil material,
shapes and sizes



Universal usage

For difficult substrates/cores
and other wrapping materials



High initial tack and green strength

Strongest adhesion –
high peel strength



Fast set speed

Forms an extremely strong
bond with a fast set time



Superior service performance

Water resistant, high heat resistant
and cold temperature flexibility



3 NEW
PUR ADHESIVES

HENKEL'S
COMPREHENSIVE
PORTFOLIO FOR
PROFILE
WRAPPING

NEW TECHNOMELT® PUR 6300 SERIES

SUPERIOR BOND STRENGTH FOR MULTI CORE AND SUBSTRATE PROFILE WRAPPING

The new TECHNOMELT® PUR 6300 Series includes three high performance, polyurethane reactive hotmelt adhesives. TECHNOMELT® PUR 6338, 6348 and 6358, provide universal usage and the flexibility for an adhesive to meet all your dynamic profile wrapping needs. Learn more about how our comprehensive PUR adhesive solutions can help you.

[CLICK HERE
FOR MORE INFO](#)

Henkel

TECHNOMELT® 6300 SERIES - SUPERIOR BOND STRENGTH FOR MULTI CORE AND SUBSTRATE USE

ADHESION STRENGTH: 90° PEEL @ 24 HOURS										LEGEND	
PRODUCT NAME	CORE					FOIL				GOOD	NOT RECOMMENDED
	MDF	PVC	PS	PVC*	PS*	VINYL	CPL	PAPER	PET		
TECHNOMELT PUR 6338	■	■	■	■	■	■	■	■	<12mil	MDF – Medium Density Fiberboard PVC – Polyvinyl Chloride PS – Polystyrene CPL – Continuous Pressure Laminate PET – Polyethylene Terephthalate	
TECHNOMELT PUR 6348	■	■	■	■	■	<8mil		<8mil	<8mil		
TECHNOMELT PUR 6358	■	■	■	■	■	<10mil		<10mil	<10mil		

* Corona treated cores

TECHNOMELT® 6300 SERIES ADVANTAGES:

- Open time: Medium (6338), Long (6348, 6358)
- Low coating weight
- Good wetting
- Clean running
- Cures into an insoluble, thermoset film
- Very high heat (>150°C), water resistant, and cold flexibility



Comes in pails and drums

CUSTOMER BENEFITS:

- 6300 Series allows for universal usage for a wide range of foils and substrate compatibility
- Provides adhesion to difficult substrates/cores, including MDF, PVC, and PS
- Consistent production with all machine speed application methods (roller, extrusion, nozzle)



HENKEL CORPORATION
10 Finderne Avenue, Suite B
Bridgewater, NJ 08807
Tel: 908.685.7000
www.henkel-adhesives.com
construction_namx@henkel.com

CLICK HERE
FOR MORE INFO

All marks used are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.
® = registered in the U.S. Patent and Trademark Office. © 2021 Henkel Corporation. All rights reserved.

